

# AWWA C503, WET BARREL

# HYDRANT – OPTIONS

## AWWA C503 WET BARREL HYDRANT OPTIONS

• Style

- 24T– Threaded Ductile Iron ( High Pressure )
- 24S – Stainless Steel

• Pressure Class

- UL/FM-200 PSI
- UL/FM-250, AWWA-350 PSI

• Pumper/Outlet Options

- PHH– 1 Pumper (P), 2 Hose (H)
- PHN– 1 Pumper (P), 1 Hose (H), No second Hose (N)
- PPH– 2 Pumper (P), 1 Hose (H)

• Chains

- With Chains
- With Cables
- Without Chains

• Pumper Nozzle

- Size \_\_\_\_\_
- Thread type \_\_\_\_\_

• Hose Nozzle

- Size \_\_\_\_\_
- Thread type \_\_\_\_\_

• Operating Nut

- Size \_\_\_\_\_
- Shape \_\_\_\_\_

• Bolting

- Zinc Plated ( Standard )
- 304 Stainless Steel
- 316 Stainless Steel

• Mounting Hardware

- Zinc Plated ( Standard )
- 304 Stainless Steel
- 316 Stainless Steel

• Opening Direction

- Open Left ( Standard )

• Optional Break Flange

- Outlet Drill Pattern \_\_\_\_\_
- Inlet Drill Pattern \_\_\_\_\_

• Inlet Drill Pattern

- 6 Hole ( AWWA C503 )
- 8 Hole ( ASME B16.1, Class 125 )
- San Diego

• Color

- Body
- Hose Cap
- Pumper Cap
- Dummy Nuts
- Special Color

• FlowGuard II™ ( Optional )

- Outlet Drill Pattern
- Inlet Drill Pattern
- 316 Bolting
- Color

• Adapter Kit for Non AVK Hydrant

- Specify required drilling \_\_\_\_\_

• Special Options – All special options must be approved by AVK

Customer: \_\_\_\_\_

Municipality: \_\_\_\_\_

Engineer: \_\_\_\_\_




Requested By: \_\_\_\_\_

Date: \_\_\_\_\_

Approval Name: \_\_\_\_\_

Signature: \_\_\_\_\_

Title: \_\_\_\_\_

| Type                                                                                                               | AVK Ref. #                                                                         | Size                           | Weight |     | Price |
|--------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------------------------|--------|-----|-------|
|                                                                                                                    |                                                                                    |                                | kg     | lb  | US \$ |
| <b>Series 24T/PHH</b><br><b>(2492) Wet barrel hydrant</b><br><b>Ductile Iron, High Pressure</b>                    |   | 24T/PHH 2 x 2.5" and 1 x 4"    | 62     | 136 | 4,085 |
| To AWWA C503<br>UL Listed<br>FM Approved<br>2 Hose Nozzles<br>1 Pumper Nozzle<br>UL/FM - 250 PSI<br>AWWA - 350 PSI |                                                                                    | 24T/PHH 2 x 2.5" and 1 x 4.5"  | 62     | 136 | 4,085 |
| <b>Series 24T/PHN</b><br><b>(2472) Wet barrel hydrant</b><br><b>Ductile Iron, High Pressure</b>                    |   | 24T/PHN 1 x 2.5" and 1 x 4"    | 57     | 126 | 2,491 |
| To AWWA C503<br>UL Listed<br>FM Approved<br>1 Hose Nozzle<br>1 Pumper Nozzle<br>UL/FM - 250 PSI<br>AWWA - 350 PSI  |                                                                                    | 24T/PHN 1 x 2.5" and 1 x 4.5"  | 57     | 126 | 2,491 |
| <b>Series 24T/PPH</b><br><b>(2422) Wet barrel hydrant</b><br><b>Ductile iron</b>                                   |  | 24IT/PPH 1 x 2.5" and 2 x 4"   | 58     | 127 | 4,575 |
| To AWWA C503<br>UL Listed<br>1 Hose Nozzle<br>2 Pumper Nozzles<br>UL - 250 PSI<br>AWWA - 350 PSI                   |                                                                                    | 24IT/PPH 1 x 2.5" and 2 x 4.5" | 58     | 127 | 4,575 |
|                                                                                                                    |                                                                                    | 6 hole bolting options only    |        |     |       |

AWWA C503, DUCTILE IRON, WET BARREL HYDRANTS